

MATERIAL SAFETY DATA SHEET

S-1000, 1100, 1300 MULTI PURPOSE THIN SET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER: SUMMITVILLE LABORATORIES, INC.
PO BOX 90
81 ARBOR ROAD
MINERVA, OH 44657

INFORMATION PHONE 330-868-6463
EMERGENCY PHONE 330-223-1511
24 HOUR SPILL AND EMERGENCY PHONE: 800-424-9300chemtrec

PRODUCT NAME: S-1000, 1100, 1300 MULTI PURPOSE T
PRODUCT NUMBER: 58-00-9180
UPC NUMBER:
PREPARED BY: Safety Manager
DATE PREPARED: 3/29/00
LAST REVISION: 9/1/99
SYNONYMS: LATEX MODIFIED THIN SET MORTAR

UN NUMBER: Not Reg
N. AMER. EMER GUIDE #: N/R
HAZARD CLASS: Not Reg
PACKING GROUP: Not Reg
PROPER SHIPPING NAME: Not Regulated

2. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS # | OSHA PEL | ACGIH TLV |
|----------------------------------|----------|--|--------------------------------|
| PORTLAND CEMENT MIXTURE | 65997151 | PEL = (TOTAL DUST) 15 MG/M3; (RESPIRABLE FRACTION) 5mg/M3 | TLV = 10mg/M3 |
| SILICA, CRYSTALLINE - QUARTZ | 14808607 | PEL = SEE TABLE Z-3 | TLV = 0.1mg/M3 respirable dust |
| Vinyl Acetate/Ethylene Copolymer | 24937788 | N/E | N/E |

3. HAZARDOUS IDENTIFICATION

EMERGENCY OVERVIEW: This material is not flammable or reactive; but should be stored in a dry area to preserve material.

POTENTIAL HEALTH EFFECTS

EYE CONTACT: Can cause severe eye irritation

INHALATION: Prolonged exposure to silicon dioxide dust can cause delayed (chronic) lung injury (silicosis).

INGESTION: May cause severe and permanent damage to mouth, throat, stomach, and digestive tract.

SKIN CONTACT: Prolonged exposure may cause skin irritation.

SIGNS AND SYMPTOMS OF EXPOSURE:

Shortness of breathing, confused behavior, redness of skin, swelling of tissues, watery eyes, nausea.

4. FIRST AID MEASURES

- EYE CONTACT:** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and tested by medical personnel.
- INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
- INGESTION:** If swallowed, drink large amounts of water and induce vomiting. Never give anything by mouth to an unconscious person. Seek medical attention immediately.
- SKIN CONTACT:** Wash affected area with soap and water. If irritation persists, get medical attention.

AGGRAVATED MEDICAL CONDITIONS:

Frequent and prolonged contact with eyes and skin can cause irritation. Prolonged exposure above guidelines may cause silicosis.

SUPPLEMENTAL HEALTH INFORMATION:

N/A

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASH POINT: N/A

FLASH POINT METHOD USED: N/A

AUTOIGNITION: N/A

LEL:

UEL:

EXTINGUISHING MEDIA:

Generally non-flammable. Use appropriate media for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES:

N/A. Will not burn.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

N/A

COMBUSTION PRODUCTS:

none known

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED:

Keep dust to a minimum. Material may be swept by personnel wearing appropriate protective equipment.

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Avoid storing material in areas where it will be exposed to high humidity and/or moisture. Material will solidify when exposed to moisture.

OTHER PRECAUTIONS:

N/A

8. EXPOSURE CONTROL/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

Wear appropriate respirator complying with NIOSH and other appropriate regulations.

VENTILATION:

Controlling airborne concentration below the ACGIH TLV exposure guideline is recommended. Use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

PROTECTIVE GLOVES:

Wear gloves as appropriate for sensitive skin.

EYE PROTECTION:

Safety glasses with side shields (or goggles) as appropriate.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

N/A

WORK / HYGENIC PRACTICES:

Use good personal hygiene when handling this product. Wash hands after use, before smoking, or using the toilet.

ENGINEERING CONTROLS:

Good ventilation should be sufficient to control airborne levels.

EXPOSURE GUIDELINES:

N/A

9. PHYSICAL AND CHEMICAL PROPERTIES

SOLUABILITY IN WATER: Portland cement portion reacts with water

APPEARANCE AND ODOR: Powder. Light gray to white color. Little to no odor.

| | | | |
|---------------------------|------|--------------------------|-----|
| BOILING POINT: | N/A | PERCENT VOLATILE: | N/A |
| VAPOR PRESSURE: | N/A | PH: | |
| EVAPORATION: | N/A | MOLECULAR WEIGHT: | |
| POUNDS PER GALLON: | N/A | VAPOR DENSITY: | N/A |
| SPECIFIC GRAVITY: | ~3.0 | OTHER PROPERTIES: | |
| MELTING POINT: | N/A | | |
| FREEZING POINT: | N/A | | |

10. STABILITY AND REACTIVITY

STABLE: Stable

INCOMPATIBILITY:

Avoid uncontrolled contamination with strong acids and corrosive materials.

HAZARDOUS DECOMPOSITION OR BY PRODUCTS:

N/A

HAZARDOUS POLYMERIZATION: Will Not Occur

11. TOXICOLOGY INFORMATION

N/A

12. ECOLOGICAL INFORMATION

N/A

13. DISPOSAL CONSIDERATIONS

May be disposed of in a sanitary landfill. Always follow appropriate Federal, District, State, Regional, and Local disposal regulations.

14. TRANSPORTATION INFORMATION

DOT CLASSIFICATION: Not Regulated

UN NUMBER: Not Reg

HAZARD CLASS: Not Reg

PACKING: Not Reg

GUIDE NUMBER: N/R

PROPER SHIPPING NAME: Not Regulated

15. REGULATORY INFORMATION

No information available.

16. OTHER INFORMATION

HMS INFORMATION: HEALTH: 3 FLAMMABILITY: 0 REACTIVITY: 0 PROTECTIVE: E

Disclaimer

The information contained herein is based on the data available to us and is believed to be accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injuries from the use of the product described herein.