

GROUT SELECTION GUIDE

		GROUT TYPE									
		S-700 Portland Cement/ Sand (5) (7)		Dry-Set (5) (7)	Latex Grout		Epoxy (1) (4)	Epoxy (1) (4)	Furan (1) (4)		
					S-700/S-775 (7)						
		Wall Use	Floor Use	S-667	S-710 (6) (7)	Wall Use	Floor Use	S-400 Series S-500 S-600 S-5000	S-500 Wall and Counter	S-4000 Series	
A rubber faced trowel should be used when grouting glazed tile with sanded grout.											
		TILE TYPE	GLAZED WALL TILE (More than 7% absorption.)		*	*	*	*	*	*	*
		CERAMIC MOSAICS	*	*	*	*	*	*	*	*	
		MARBLE			*				*		
		PORCELAIN	*	*		*	*	*	*		
QUARRY, PAVER, PACKING HOUSE TILE	*	*		*	*	*		*			
AREAS OF USE	Dry or limited water exposure	*	*	*	*	*	*	*	*		
	Wet Areas	*	*	*	*	*	*	*	*		
	Exteriors	*	*	*	*	*	*	*	*		
PERFORMANCE	Stain Resistance (3)*	2	2	2	4	3	5	5	5		
	Wet Areas	2	2	2	5	3	5	5	3		
	Exteriors	3	2	3	4	2	5	5	Black Only		

- (1) Mainly used for chemical resistant properties.
- (2) Special cleaning procedures and materials recommended.
- (3)* Five performance ratings—best to minimal (5 4 3 2 1).
- (4) S-400, S-500, S-600, S-5000 and S-4000 Series can be used where steam cleaning expected (up to 350°F).
- (5) Can be mixed with S-775 Acrylic Admixture.
- (6) S-120 should not be used with S-710 Dry Latex Grout.
- (7) All colored grouts that contain cement will discolor on floors over time, recommend neutral colors only.