



## SL-55 COLOR ENHANCING SEALER

### PRODUCT DESCRIPTION:

SL-55 is a one part penetrating sealant for use on grout, stone and brick pointing mortar, porous stone, brick and clay materials. SL-55 deepens and darkens the color of materials and provides a low gloss or sheen. This product is ideally suited for long-term hiding of waterborne stains and greasy food stains.

### APPLICATION:

**Test the sealer on a potential substrate before using to insure that the cosmetic changes will be suitable.** Always test in an inconspicuous area or an extra piece of material. Insure that surfaces to be treated are clean and thoroughly dry. If surface(s) has/have been acid washed, be certain all residues have been neutralized and rinsed clean. SL-55 can be applied to cementitious grouts 14 days after installation of grout. While wearing latex or similar impervious gloves, wipe a thin, uniform coat onto surface with a clean cloth or brush. Wipe up all excess after permitting SL-55 to soak on floor for a few minutes. Dry excess can be removed with Summitville SL-100 Tile and Grout Cleaner. Allow floor to cure for one week uncovered, prior to cleaning floor. Do not use harsh cleaners for two weeks after application of SL-55. Summitville recommends application of SL-55 in sections to allow traffic through area while SL-55 is curing.

### FIRST AID:

#### Keep out of reach of children.

Irritant to eyes and mucous membranes. Harmful if swallowed.

EYE CONTACT: Immediately flush with large amounts of water. Contact a physician if irritation persists.

SKIN CONTACT: Wash contaminated area with soap and water. Remove contaminated clothing.

INGESTION: If swallowed, drink large amounts of water or milk. See physician immediately. **DO NOT INDUCE VOMITING.**

### PACKAGING:

SL-55 is available in:

1-quart units

1-gallon units

5-gallon units

### COVERAGE:

	Approx tile coverage per coat, per gallon	Minimum Dry Hours @ 72°F After:	Minimum Hrs Before Floor Traffic @ 72°F:
Honed Marble	200-350 sq. ft	2-4	16
Dense Quarry Tile	150-225 sq. ft	3-5	16
Porous Quarry Tile	50-125 sq. ft	6-8	16
Slate	150-200 sq. ft	3-5	16
Concrete (smooth)	50-150 sq. ft	6-8	16
Polished Granite	400-500 sq. ft	2-4	16

Tile Size/Grout Only	Grout width 1/8" sq. ft per coat, per gallon	Grout width 1/4" sq. ft per coat, per gallon
4 x 4	2400	960
8 x 8	2960	1360
12 x 12	3200	1520
16 x 16	3600	1680