



SL-86 NON-AMMONIATED CLEANER, DEGREASER & ACRYLIC SEALANT REMOVER

PRODUCT DESCRIPTION:

SL-86 is a specially formulated cleaner, degreaser & acrylic sealant remover designed to remove acrylic floor sealers, urethane fortified topcoats and waxes. SL-86 will also clean grease and grime from tile and stainless steel surfaces. SL-86 is used to prepare tile surface for SL-80 Acrylic Floor Sealer. This product does not contain the harsh smell of ammonia. SL-86 can be used in enclosed areas where ammonia vapors can be a problem.

LIMITATIONS:

Avoid exposing this product to wood finishes or soft coatings on items such as brass to prevent damage to the coating. This is an industrial/institutional cleaning product. Do not mix with other household cleaners. Wear rubber gloves and eye protection. **Caution!** Irritant to eyes and mucous membranes. Harmful if swallowed. If ingested, give one or two glasses of water and call physician. **DO NOT** induce vomiting. In case of contact with eyes, flush thoroughly for at least 15 minutes. If irritation persists, get medical attention.

APPLICATION:

1. Sweep floors to be cleaned or stripped, free of dirt and debris.
2. Add ½ cup of SL-86 to a gallon of clean, hot water.
3. Apply SL-86 liberally to the floor and allow the solution to stand for one or two minutes.
4. For stubborn areas, use a floor scrubber, stiff bristled brush or plastic scouring pad.
5. Remove SL-86 solution and rinse with clean water.
6. Repeat as necessary.

OTHER SL - 86 USES:

- Mix SL-86 and hot water and use as a soaker bath for equipment with dried on grease build-up.
- Cleans stainless steel exhaust hood filter screens too.
- For soak-in-place applications, please use SL-86 Gel.
- SL-86 will also strip acrylic and urethane modified coatings from flooring, concrete patios, driveways, and walkways.
- SL-86 can be used to strip road tar and wax from automobile bodies.

PACKAGING:

SL-86 is available in:
1-quart plastic bottles (12 to a case)
1-gallon bottles (6 to a case)